

## **JUVENILE FISH SCREEN CRITERIA**

Developed by  
National Marine Fisheries Service  
Environmental & Technical Services Division  
Portland, Oregon  
Revised February 16, 1995

### **I. GENERAL CONSIDERATIONS:**

This document provides guidelines and criteria to be utilized in the development of functional designs of downstream migrant fish passage facilities for hydroelectric, irrigation, and other water withdrawal projects. This material has been prepared by the National Marine Fisheries Service (NMFS) as a direct result of responsibilities for prescribing fishways (including fish screen and bypass systems) under Section 18 of the Federal Power Act, administered by the Federal Energy Regulatory Commission (FERC). This material is also applicable for projects that are undergoing consultation with the NMFS, pursuant to responsibilities for protecting fish under the Endangered Species Act (ESA).

Since these guidelines and criteria are general in nature, there may be cases where site constraints or extenuating circumstances dictate that certain criteria be waived or modified. Conversely, where there is a need to provide additional protection for fish, site-specific criteria may be added. These circumstances will be considered by NMFS on a project-by-project basis.

In designing an effective fish screen facility, the swimming ability of the fish is a primary consideration. Research has shown that swimming ability of fish varies and may depend upon a number of factors relating to the physiology of the fish, including species, size, duration of swimming time required, behavioral aspects, migrational stage, physical condition and others, in addition to water quality parameters such as dissolved oxygen concentrations, water temperature, lighting conditions, and others. For this reason, screen criteria must be expressed in general terms.

To minimize risks to anadromous fish at some locations, the NMFS may require investigation (by the project sponsors) of important and poorly defined site-specific variables that are deemed critical to development of the screen and bypass design. This investigation may include factors such as fish behavioral response to hydraulic conditions, weather conditions (ice, wind, flooding, etc.), river stage-discharge relationships, seasonal operational variability, potential for sediment and debris problems, resident fish populations, potential for creating predation opportunity, and other information. The size of salmonids present at a potential screen site usually is not known, and can change from year to year based on flow and temperature conditions. Thus, adequate data to describe the size-time relationship requires substantial sampling efforts over a number of years. The NMFS will assume that fry-sized salmonids and low water temperatures are present at all sites and apply the appropriate criteria listed below, unless adequate biological investigation proves otherwise. The burden-of-proof is the responsibility of the owner of the screen facility.

Proposed facilities which could have particularly significant impacts on fish, and new unproven juvenile fish protection designs, frequently require: 1) development of a biological basis for the concept; 2) demonstration of favorable fish behavioral response in a laboratory setting; 3) an acceptable plan for evaluating the prototype installation; and 4) an acceptable alternate plan developed concurrently for a screen and bypass system satisfying these criteria, should the prototype not adequately protect fish. Additional information on unproven juvenile fish protection devices can be found in "Experimental Fish Guidance Devices," Position Statement of the National Marine Fisheries Service, Northwest Region, January 6, 1995.

Screen and bypass criteria for juvenile salmonids are provided below. Specific exceptions to these criteria occur in the design of small screen and bypass systems (less than 25 cubic feet per second). These are listed in Section K, Modified Criteria for Small Screens.

Striped bass, herring, shad, and other anadromous fish species may have eggs and/or very small fry which are moved with any water current (tides, streamflows, etc.). Installations where these species are present may require special screen and/or bypass facilities, including micro-screens and require individual evaluation of the proposed project. In instances where local regulatory agencies require more stringent screening requirements for species of resident or anadromous fish, the NMFS will generally defer to the more conservative criteria.

## II. GENERAL PROCEDURAL GUIDELINES

A functional design should be developed that defines type, location, size, hydraulic capacity, method of operation, and other pertinent juvenile fish screen facility characteristics. In the case of applications to be submitted to the FERC and consultations under the ESA, a functional design for juvenile (and adult) fish passage facilities must be developed and submitted as part of the application. It must reflect the NMFS input and design criteria and be acceptable to the NMFS. Functional design drawings must show all pertinent hydraulic information, including water surface elevations and flows through various areas of the structures. Functional design drawings must show general structural sizes, cross-sectional shapes, and elevations. Types of materials must be identified where they will directly affect fish. The final detailed design shall be based on the functional design, unless changes are agreed to by the NMFS.

All juvenile passage facilities shall be designed to function properly through the full range of hydraulic conditions in the lake, tidal area, or stream and in the diversion, and shall account for debris and sedimentation conditions which may occur.

## III. SCREEN CRITERIA FOR JUVENILE SALMONIDS

### A. Structure Placement

#### 1. Streams and Rivers:

a. Where physically practical and biologically desirable, the screen shall be constructed at the diversion entrance with the screen face generally parallel to river flow. Physical factors that may preclude screen construction at the diversion entrance include excess river gradient, potential for

damage by large debris, and potential for heavy sedimentation. For screens constructed at the bankline, the screen face shall be aligned with the adjacent bankline and the bankline shall be shaped to smoothly match the face of the screen structure to prevent eddies in front, upstream, and downstream of the screen. If trash racks are used, sufficient hydraulic gradient is required to route juvenile fish from between the trash rack and screens to safety.

b. Where installation of fish screens at the diversion entrance is not desirable or impractical, the screens may be installed in the canal downstream of the entrance at a suitable location. All screens installed downstream from the diversion entrance shall be provided with an effective bypass system approved by NMFS, designed to collect juvenile fish and safely transport them back to the river with minimum delay. The angle of the screen to flow should be adequate to effectively guide fish to the bypass (see Section F, Bypass Layout).

## 2. Lakes, Reservoirs and Tidal areas:

a. Intakes shall be located offshore where feasible to minimize fish contact with the facility. Water velocity from any direction toward the screen shall not exceed allowable approach velocities (see Section B, Approach Velocity). When possible, intakes shall be located in areas with sufficient sweeping velocity to minimize sediment accumulation in or around the screen and to facilitate debris removal and fish movement away from the screen face (see Section C, Sweeping Velocity).

b. If a screened intake is used to route fish past a dam, the intake shall be designed to withdraw water from the most appropriate elevation based on providing the best juvenile fish attraction and appropriate water temperature control downstream of the project. The entire range of forebay fluctuation shall be accommodated in design, unless otherwise approved by the NMFS.

B. Approach Velocity - Definition: Approach velocity is the water velocity component perpendicular to and approximately three inches in front of the screen face.

1. Salmonid fry [less than 2.36 inches {60.0 millimeters (mm)} in length]: The approach velocity shall not exceed 0.40 feet per second (fps) {0.12 meters per second (mps)}.

2. Salmonid fingerling {2.36 inches (60.0 mm) and longer}: The approach velocity shall not exceed 0.80 fps (0.24 mps).

3. The total submerged screen area required (excluding area affected by structural components) is calculated by dividing the maximum diverted flow by the allowable approach velocity (also see Section K, Modified Criteria for Small Screens).

4. The screen design must provide for uniform flow distribution over the screen surface, thereby minimizing approach velocity. This may be accomplished by providing adjustable porosity control on the downstream side of screens, unless it can be shown unequivocally (such as with a physical hydraulic model study) that localized areas of high velocity can be avoided at all flows.

C. Sweeping Velocity - Definition: Sweeping velocity is the water velocity component parallel and adjacent to the screen face.

1. Sweeping velocity shall be greater than the approach velocity. This is accomplished by angling the screen face at less than 45° relative to flow (also see Section K, Modified Criteria for Small Screens). This angle may be dictated by site specific canal geometry, hydraulic, and sediment conditions.

#### D. Screen Face Material

1. Fry criteria - If biological justification can not be provided to demonstrate the absence of fry-sized salmonids {less than 2.36 inches (60.0 mm)} in the vicinity of the diversion intake leading to the screen, fry will be assumed present and the following criteria apply for screen material:

- a. Perforated plate: Screen openings shall not exceed 3/32 or 0.0938 inches (2.38 mm).
- b. Profile bar screen: The narrowest dimension in the screen openings shall not exceed 0.0689 inches (1.75 mm) in the narrow direction.
- c. Woven wire screen: Screen openings shall not exceed 3/32 or 0.0938 inches (2.38 mm) in the narrow direction (example: 6-14 mesh).
- d. Screen material shall provide a minimum of 27% open area.

2. Fingerling criteria - If biological justification can be provided to demonstrate the absence of fry-sized salmonids {less than 2.36 inches (60.0 mm)} in the vicinity of the diversion intake leading to the screen, the following criteria apply for screen material:

- a. Perforated plate: Screen openings shall not exceed 1/4 or 0.25 inches (6.35 mm).
- b. Profile bar screen: The narrowest dimension in the screen openings shall not exceed 1/4 or 0.25 inches (6.35 mm) in the narrow direction.
- c. Woven wire screen: Screen openings shall not exceed 1/4 or 0.25 inches (6.35 mm) in the narrow direction.
- d. Screen material shall provide a minimum of 40% open area.

3. The screen material shall be corrosion resistant and sufficiently durable to maintain a smooth uniform surface with long term use.

#### E. Civil Works and Structural Features

1. The face of all screen surfaces shall be placed flush (to the extent possible) with any adjacent screen bay, pier noses, and walls to allow fish unimpeded movement parallel to the screen face and ready access to bypass routes.

2. Structural features shall be provided to protect the integrity of the fish screens from large debris. Provision of a trash rack, log boom, sediment sluice, and other measures may be needed. A reliable, ongoing preventative maintenance and repair program is necessary to assure facilities are kept free of debris and that screen mesh, seals, drive units, and other components are functioning correctly.
3. Screen surfaces shall be constructed at an angle to the approaching flow, with the downstream end of the screen terminating at the entrance to the bypass system.
4. The civil works shall be designed in a manner that eliminates undesirable hydraulic effects (such as eddies and stagnant flow zones) that may delay or injure fish or provide predator habitat or predator access. Upstream training wall(s), or some acceptable variation thereof, shall be utilized to control hydraulic conditions and define the angle of flow to the screen face. Large facilities may require hydraulic modeling to identify and correct areas of concern.

#### F. Bypass Layout

1. The screen and bypass shall work in tandem to move out-migrating salmonids (including adults) to the bypass outfall with a minimum of injury or delay. The bypass entrance shall be located so that it can easily be located by out-migrants. Screens placed in diversions shall be constructed with the downstream end of the screen terminating at a bypass entrance. Multiple bypass entrances (intermediate bypasses) shall be employed if the sweeping velocity will not move fish to the bypass within 60 seconds, assuming fish are transported at this velocity.
2. The bypass entrance and all components of the bypass system shall be of sufficient size and hydraulic capacity to minimize the potential for debris blockage.
3. In order to improve bypass collection efficiency for a single bank of vertically-oriented screens, a bypass training wall shall be located at an angle to the screens, with the bypass entrance at the apex and downstream-most point. This will aid fish movement into the bypass by creating hydraulic conditions that conform to observed fish behavior. For single or multiple vee screen configurations, training walls are not required, unless a intermediate bypass is used (see Section F, Bypass Layout, Part 1).
4. In cases where there is insufficient flow available to satisfy hydraulic requirements at the bypass entrance (entrances) for the main screens, a secondary screen may be required. This is a screen located in the main screen bypass which allows the prescribed bypass flow to be used to effectively attract fish into the bypass entrance(s) and then allow for all but a reduced residual bypass flow to be routed back (by pump or gravity) for the primary diversion use. The residual bypass flow (not passing through the secondary screen) would then convey fish to the bypass outfall location or other destination.
5. Access is required at locations in the bypass system where debris accumulations may occur.

6. The screen civil works floor shall be designed to allow fish to be routed back to the river safely, if the canal is dewatered. This may entail a sumped drain with a small gate and drain pipe, or similar provisions.

#### G. Bypass Entrance

1. Each bypass entrance shall be provided with independent flow-control capability, acceptable to NMFS.

2. The minimum bypass entrance flow velocity must be greater than or equal to the maximum flow velocity vector resultant upstream of the screens. A gradual and efficient acceleration of flow into the bypass entrance is required to minimize delay by out-migrants.

3. Ambient lighting conditions are required at, and inside of, the bypass entrance and should extend downstream to the bypass flow control.

4. The bypass entrance must extend from the floor to the canal water surface.

#### H. Bypass Conduit Design

1. Bypass pipes shall have smooth surfaces and be designed to provide conditions that minimize turbulence. Bypass conduits shall have a smooth joint design to minimize turbulence and the potential for fish injury and shall be satisfactory to the NMFS.

2. Fish shall not be pumped within the bypass system.

3. Fish shall not be allowed to free-fall within a confined shaft in a bypass system.

4. Pressures in the bypass pipe shall be equal to or above atmospheric pressures.

5. Bends shall be avoided in the layout of bypass pipes due to the potential for debris clogging. Bypass pipe center-line radius of curvature (R/D) shall be greater than or equal to 5. Greater R/D may be required for super-critical velocities.

6. Bypass pipes or open channels shall be designed to minimize debris clogging and sediment deposition and to facilitate cleaning as necessary. Therefore, the required pipe diameter shall be greater than or equal to 24 inches {0.610 meters (m)}, and pipe velocity shall be greater than 2.0 fps (0.610 mps), unless otherwise approved by the NMFS, for the entire operational range (also see Section K, Modified Criteria for Small Screens, Part 4).

7. Closure valves of any type are not allowed within the bypass pipe, unless approved by NMFS.

8. The minimum depth of open-channel flow in a bypass conduit shall be greater than or equal to 0.75 feet (0.23 m), unless otherwise approved by the NMFS (also see Section K, Modified Criteria for Small Screens, Part 5).

9. Sampling facilities installed in the bypass conduit shall not impair normal operation of the facility.

10. The bypass pipe hydraulics should not produce a hydraulic jump within the pipe.

#### I. Bypass Outfall

1. Bypass outfalls should be located such that ambient river velocities are greater than 4.0 fps (1.2 mps).

2. Bypass outfalls shall be located to minimize avian and aquatic predation in areas free of eddies, reverse flow, or known predator habitat.

3. Bypass outfalls shall be located where the receiving water is of sufficient depth (depending on the impact velocity and quantity of bypass flow) to ensure that fish injuries are avoided at all river and bypass flows.

4. Maximum bypass outfall impact velocity (including vertical and horizontal velocity components) shall be less than 25.0 fps (7.6 mps).

5. The bypass outfall discharge into tailrace shall be designed to avoid adult attraction or jumping injuries.

#### J. Operations and Maintenance

1. Fish screens shall be automatically cleaned as frequently as necessary to prevent accumulation of debris. The cleaning system and protocol must be effective, reliable, and satisfactory to the NMFS. Proven cleaning technologies are preferred.

2. Open channel intakes shall include a trash rack in the screen facility design which shall be kept free of debris. In certain cases, a satisfactory profile bar screen design can substitute for a trash rack.

3. The head differential to trigger screen cleaning for intermittent type cleaning systems shall be a maximum of 0.1 feet (0.03 m) or as agreed to by the NMFS.

4. The completed screen and bypass facility shall be made available for inspection by NMFS, to verify compliance with the design and operational criteria.

5. Screen and bypass facilities shall be evaluated for biological effectiveness and to verify that hydraulic design objectives are achieved.

#### K. Modified Criteria for Small Screens (Diversion flow less than 25 cfs)

The following criteria vary from the criteria listed above and apply to smaller screens. Twenty-five cfs is an approximate cutoff; however, some smaller diversions may be required to apply

more universal criteria listed above, while some larger diversions may be allowed to use the "small screen" criteria listed below. This will depend on site constraints.

1. The screen area required is shown in Section B, Approach Velocity, Parts 1, 2 and 3. Note that "maximum" applies to the greatest flow diverted, not necessarily the water right.

2. Screen orientation:

a. For screen lengths less than or equal to 4 feet, screen orientation may be angled or perpendicular relative to flow.

b. For screen lengths greater than 4 feet, screen-to-flow angles must be less than or equal to 45 degrees (see Section C, Sweeping Velocity, Part 1).

c. For drum screens, the design submergence shall be 75% of drum diameter. Submergence shall not exceed 85%, nor be less than 65% of drum diameter.

3. The minimum bypass pipe diameter shall be 10 inches, unless otherwise approved by NMFS.

4. The minimum allowable pipe depth is 0.15 feet (1.8 inches or 4.6 cm) and is controlled by designing the pipe gradient for minimum bypass flow.

Questions concerning this document can be directed to NMFS Environmental and Technical Services Division Engineering staff, at 503-230-5400.

Adopted,

William Stelle, Jr. Date  
Regional Director